

A class	Product Information AHB682IX
MODEL	AHB682IX
Energy efficiency classes of domestic range hoods (A-G)	A
Annual Energy Consumption - AEC hood (kWh/a)	30
Fluid Dynamic Efficiency classes for domestic range hoods (A-G)	A
Lighting Efficiency classes (A-G)	A
The Grease Filtering Efficiency classes (A-G)	C
Sound power level L WA - (dB)	62
Time increase factor - f	0,9
Fluid Dynamic Efficiency - FDE hood	31,6
Energy Efficiency Index - EEI hood	47,4
Measured air flow rate at best efficiency point - Q BEP (m ³ /h)	287,9
Measured air pressure at best efficiency point P BEP (Pa)	323
Measured electric power input at best efficiency point - W BEP (W)	81,8
Nominal power of the lighting system - W L (W)	3,8
Average illumination of the lighting system on the cooking surface - E middle (lux)	139
Lighting Efficiency LE hood - (lux/Watt)	36,6
Grease Filtering Efficiency GFE hood - (%)	76
Minimum airflow (Q min)	204
Maximum air flow - Q max (m ³ /h)	606
Airflow -boost (Q boost)	-
Minimum sound power level L WA - (dB)	50
Maximum sound power level L WA - (dB)	62
Sound power level-boost L WA - (dB) Measured	-
power consumption off mode P o (W)	0,34
Measured power consumption in standby mode - P s (W)	-
Product fiche according to "COMMISSION DELEGATED REGULATION (EU) No 65/2014 "	